

PPMC-111C/CFP

Programmable Stepper

Motor Control LSI

Ampere Inc.

PPMC-111C/CFP

Programmable Stepper Motor Control LSI

Table of contents

1. SPECIFICATIONS AND FUNCTIONS	1-1
1-1. Description	1-1
1-2. Specification	1-2
1-3. Concepts and Performance of PPMC-111	1-3
1-3-1. Pulse rate and motor speed	1-3
1-3-2. Acceleration/ deceleration method	1-3
1-4. Differences from PPMC-100 series	1-4
1-4-1. Additional of acceleration/deceleration methods	1-4
1-4-2. Higher speed	1-5
1-4-3. Addition of commands	1-5
1-4-4. Addition of error codes	1-5
1-4-5. Elimination of phase excitation signals	1-5
1-4-6. Addition of status register bits	1-5
2. TERMINAL ASSIGNMENT	2-1
2-1. Signal description of system hardware	2-5
2-1-1. RESET	2-5
2-1-2. X1, X2 (Crystal oscillator)	2-5
2-2. Host interface signals	2-6
2-2-1. CS (Chip select)	2-6
2-2-2. A0 (Register select)	2-6
2-2-3. D7 - D0 (Data bus)	2-6
2-2-4. BUSC (Slave bus interface select)	2-6
2-2-5. DS, WRS (Data strobe, Write strobe)	2-7
2-2-6. R/W, RDS (Read/Write, Read strobe)	2-7
2-2-7. INT (Interrupt signal)	2-8
2-2-8. RUN (Pulse output start signal)	2-9
2-3. Motor control signals	2-9
2-3-1. DIR (Rotation direction signal)	2-9
2-3-2. POUT (Pulse train output signal)	2-9
2-3-3. Pin1, Pin2 (Internal pulse counter input)	2-9
2-3-4. HOLD (Motor hold signal)	2-9
2-4-5. RUN (Pulse output signal)	2-13
2-4. Limit and Alarm signals	2-10
2-4-1. ORG (Origin input signal)	2-10
2-4-2. FL, BL, FHL, BHL (Limit input signals)	2-10
2-4-3. ALM (Alarm input signal)	2-11
2-5. Auxiliary input/ output signals	2-12

2-5-1. AUXI0 - AUXI7 (Auxiliary input signals)	2-12
2-5-2. AUXO0 - AUXO7 (Auxiliary output signals)	2-12
2-6. SEL_TYP signal	2-12
3. CONTROL COMMAND OF PPMC-111	3-1
3-1. Host interface registers	3-2
3-1-1. Status register	3-2
3-1-2. Data register (at read)	3-4
3-1-3. Command register (write only)	3-4
3-1-4. Data register (at write)	3-5
3-2. Initialization commands	3-6
3-2-1. Initialization command for linear/ S-shaped acceleration/ deceleration method	3-7
3-2-2. Initialization command for free-curve acceleration/ deceleration method	3-10
3-3. Operation command	3-13
3-3-1. Emergency stop	3-14
3-3-2. Deceleration stop	3-15
3-3-3. Single step	3-16
3-3-4. Acceleration/ deceleration operation	3-17
3-3-5. Constant speed operation	3-19
3-3-6. Continuous constant speed operation	3-21
3-3-7. Continuous high speed operation	3-23
3-3-8. Constant speed origin search operation	3-25
3-3-9. Instantaneous speed change	3-27
3-3-10. Acceleration/ deceleration speed change	3-29
3-4. Internal register read command	3-32
3-4-1. Finish status code read command	3-32
3-4-2. Error code read command	3-34
3-4-3. Current position read command	3-37
3-4-4. Auxiliary input signal status code read command	3-39
3-4-5. Control input signal status read command	3-40
3-5. Auxiliary commands	3-41
3-5-1. Current position setting command	3-41
3-5-2. Auxiliary output command	3-43
3-5-3. High speed limit effective speed setting command	3-44
4. RATING	4-1
4-1. Absolute maximum ratings	4-1
4-2. DC Characteristics	4-1
4-3. AC Characteristics	4-2
4-3-1. RD and WR separate bus mode	4-2
4-3-2. DS and R/W bus mode	4-4
4-3-3. Alarm and limit signal input timing	4-6
4-4. Output drawing	4-7
4-4-1. Output drawing of PPMC-111CFP	4-7

4-4-2. Output drawing of PPMC-111C	4-8
5. RECOMMENDED PACKAGING CONDITIONS AND HANDLING NOTES	5-1
5-1. Temperature profile	5-1
5-1-1. Soldering iron	5-1
5-1-2. Far and medium-infrared reflow soldering	5-1
5-1-3. Case of hot air reflow soldering	5-1
5-1-4. Vapor phase reflow soldering	5-1
5-1-5. Dip soldering	5-2
5-2. Flux cleaning (Ultrasonic cleaning)	5-2
5-3. Lead forming	5-2
5-4. Coating of board	5-3
5-5. Degradation and breakdown by static charge	5-3
5-5-1. Control of working environment	5-3
5-5-2. Working notes	5-4
5-6. Requirements for service environment	5-5
5-6-1. Temperature environment	5-5
5-6-2. Humidity environment	5-5
5-6-3. Corrosive gas	5-5
5-6-4. Radioactive rays/ Cosmic rays	5-5
5-6-5. Strong electric field/ Strong magnetic field	5-5
5-6-6. Vibration/ Shock/ Stress	5-5
5-6-7. Dust/ Oil	5-5
5-6-8. Smoking/ Ignition	5-6
5-7. Requirements for design	5-6
5-7-1. Observance of maximum ratings	5-6
5-7-2. Observance of guaranteed operation range	5-6
5-7-3. Setting of unused I/O terminals	5-6
5-7-4. Latch-Up	5-6
5-7-5. Input/ Output protection	5-7
5-7-6. Interface	5-7
5-7-7. External noise	5-7
5-7-8. Other requirement	5-7